

BA-386/PRC-25 Battery

- High performance non-rechargeable Alkaline battery.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Unit contains safety vented cells



This battery meets the requirements of MIL-B-49030 for:

- Battery voltage
- Capacity test
- Electrolyte leakage
- Mechanical and thermal shock
- Vibration
- Insulation resistance

For use in	PRC-77 and PRC-25 radio sets
Replacement for	BA-3386/PRC-25, BA-4386/PRC-25, BA-5598/U, BA-386/PRC-25
Cell chemistry	Alkaline
Nominal voltage A2	A2 15.0 Volts
Nominal voltage A1	3.0V
Typical capacity	A2 15.0Ah, A1 4.9Ah
Nominal dimensions	240 x 92 x 54mm
Nominal weight	1.87kg
Connector	Floating type
Case material	Modified ABS
Operating temperature	-20°C to +55°C
Shelf life	4 years to 85% initial capacity when stored @ 20°C 5 years to 85% initial capacity when stored @ 4°C
Disposal	Environmentally safe. Check with local regulations for proper disposal

Mathews Associates, Inc.
220 Power Court
Sanford FL 32771

Phone: (407) 323-3390 Fax: (407) 323-3115
 Email: sales@maifl.com



Alkaline Manganese Dioxide