

# BB-LA6 Battery

- High performance rechargeable Sealed Lead Acid battery.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Contains internal PTC protection
- 100% final testing



Sealed Lead Acid

This battery meets the requirements of MIL-B-11188 for:

- Battery voltage
- Capacity test
- Electrolyte leakage
- Mechanical and thermal shock
- Vibration
- Insulation resistance

For use in	PRC-77, PRC-1077, PRC-1099 radio sets
Replacement for	LA-6, BB-586/U, BB-386/U, BA-386/U, BA-5598/U, TNC386 & TNC386/H
Cell chemistry	Sealed lead acid (lead calcium)
Nominal voltage	12 Volts
Typical capacity	5.5Ah
Protection	Internal re-settable fuse (PTC)
Nominal dimensions	240 x 92 x 54mm
Nominal weight	2.25kg
Connector	Floating type, 2 phosphor bronze pins fitted
Case material	Modified ABS
Operating temperature	-20°C to +55°C

**Mathews Associates, Inc.**  
**220 Power Court**  
**Sanford FL 32771**

Phone: (407) 323-3390 Fax: (407) 323-3115  
Email: [sales@maifl.com](mailto:sales@maifl.com)

