

# TNC-2188 Battery

- High performance rechargeable Nickel Cadmium battery.
- Durable high impact plastic housing and connector enclosure
- Coated cell pack for operation in tropical environments
- High reliability due to all welded construction
- Unit contains safety vented cells



**Nickel Cadmium**

This battery meets the requirements of MIL-B-49436B for:

- Battery voltage
- Capacity test
- Electrolyte leakage
- Mechanical and thermal shock
- Vibration
- Insulation resistance

This battery has the following protection feature: An internal thermal cut out to prevent cell damage due to charging at elevated temperatures.

For use in	PRC-80, PRC-730 and PRC-2200
Replacement for	TNC-2188, BA-3791
Cell chemistry	Nickel Cadmium
Nominal voltage	12.0 Volts
Typical capacity	4.5Ah
Nominal dimensions	186 x 71 x 65mm, 1.56kg
Connector	Floating 2 pin discharge connector, 2 pin charging connector. Nickel plated machined brass contacts
Case material	Modified ABS, black
Operating temperature	-20°C to +55°C
Disposal	Battery must be recycled

**Mathews Associates, Inc.**  
**220 Power Court**  
**Sanford FL 32771**

Phone: (407) 323-3390 Fax: (407) 323-3115  
Email: [sales@maifl.com](mailto:sales@maifl.com)

